



Reactor Specifications - 480 V Low Impedance (3%)

TCI Specs - MA Reactors										
480V Open 50/60Hz	HP	I rated amps	I max amps	L mh	W in	D in	H in	Wgt lb	Watts Loss	Legacy
KDRMA1L1	0.25	0.70	1.4	31.5	4.45	1.78	3.63	1.3	5.0	N/A
KDRMA2L1	0.33	0.80	1.7	27.6	4.45	1.78	3.63	1.3	6.2	N/A
KDRMA3L1	0.50	1.10	1.6	20.0	4.45	1.78	3.63	1.3	9.7	KDRA6L
KDRMA4L1	0.75	1.60	2.3	13.8	4.45	1.78	3.63	1.3	12.1	KDRA7L
KDRMA5L1	1	2.10	2.3	10.5	4.45	1.78	3.63	1.2	25.2	KDRA8L
KDRMA6L1	1.5	3.00	3.4	7.40	4.45	1.78	3.63	1.4	26.4	KDRA9L
KDRMA7L1	2	3.40	4.2	6.50	4.45	1.78	3.63	1.4	23.5	KDRA1L
KDRMA8L1	3	4.80	5.0	4.60	4.45	1.78	3.63	1.4	30.6	KDRA2L
All P/N's available in enclosures										
				Type 1	12.5	6.75	12.3	+ 10.4		
				Type 3R	10.3	12.0	11.5	+ 15.0		

Reactor Specifications - 480 V High Impedance (5%)

TCI Specs - MA Reactors										
480V Open 50/60Hz	HP	I rated amps	I max amps	L mh	W in	D in	H in	Wgt lb	Watts Loss	Legacy
KDRMA1H1	0.25	0.70	1.4	52.5	4.45	1.78	3.63	1.3	7.9	N/A
KDRMA2H1	0.33	0.80	1.4	45.9	4.45	1.78	3.63	1.5	9.2	N/A
KDRMA3H1	0.50	1.10	1.6	33.4	4.45	1.78	3.63	1.3	14.3	KDRA6H
KDRMA4H1	0.75	1.60	2.1	23.0	4.45	1.78	3.63	1.4	19.3	KDRA7H
KDRMA5H1	1	2.10	2.3	17.5	4.45	1.78	3.63	1.4	26.7	KDRA8H
KDRMA6H1	1.5	3.00	3.6	12.3	4.45	1.78	3.63	1.6	30.0	KDRA9H
All P/N's available in enclosures										
				Type 1	12.5	6.75	12.3	+ 10.4		
				Type 3R	10.3	12.0	11.5	+ 15.0		





Reactor Specifications - 600 V Low Impedance (3%)

TCI Specs - MA Reactors										
600V Open 50/60Hz	HP	I rated amps	I max amps	L mh	W in	D in	H in	Wgt lb	Watts Loss	Legacy
KDRMA41L1	0.25	0.50	0.8	55.13	4.45	1.78	3.63	1.2	3.9	n/a
KDRMA42L1	0.33	0.70	1.1	39.38	4.45	1.78	3.63	1.2	6.1	n/a
KDRMA43L1	0.50	0.90	1.6	30.6	4.45	1.78	3.63	1.1	8.5	KDRA55L
KDRMA44L1	0.75	1.30	2.1	21.2	4.45	1.78	3.63	1.3	10.9	KDRA56L
KDRMA45L1	1	1.70	2.1	16.22	4.45	1.78	3.63	1.3	16.2	KDRA50L
KDRMA46L1	1.5	2.40	3.4	11.49	4.45	1.78	3.63	1.4	17.2	KDRA51L
KDRMA47L1	2.0	2.70	3.2	10.21	4.45	1.78	3.63	1.5	20.5	KDRA46L
All P/N's available in enclosures										
			Type 1	12.5	6.75	12.3	+ 10.4			
			Type 3R	10.3	12.0	11.5	+ 15.0			

Reactor Specifications - 600 V High Impedance (5%)

TCI Specs - MA Reactors										
600V Open 50/60Hz	HP	I rated amps	I max amps	L mh	W in	D in	H in	Wgt lb	Watts Loss	Legacy
KDRMA41H1	0.25	0.50	0.8	91.9	4.45	1.78	3.63	1.3	5.9	n/a
KDRMA42H1	0.33	0.70	0.8	65.63	4.45	1.78	3.63	1.2	9.1	n/a
KDRMA43H1	0.50	0.90	1.1	51	4.45	1.78	3.63	1.5	12.9	KDRA55H
KDRMA44H1	0.75	1.30	1.6	35.3	4.45	1.78	3.63	1.6	14.6	KDRA52H
KDRMA45H1	1	1.70	2.1	27.03	4.45	1.78	3.63	1.5	27.0	KDRA50H
All P/N's available in enclosures										
			Type 1	12.5	6.75	12.3	+ 10.4			
			Type 3R	10.3	12.0	11.5	+ 15.0			

