

PART NUMBER	UL	ENCL	IMPEDANCE	RATED VOLTS	HORSE POWER	NEC AMPS	MAX CONTINUOUS AMPS	HEIGHT	WIDTH	DEPTH	TERM TYPE	TERM TORQUE	TORQUE UM	TEMP RISE	WATTS LOSS	WEIGHT
KDRA1PDR	UL Listed	Open	P	480	2	3.4	4	4	4.18	3.75	TB	10	LB-IN	115	N/A	4.00
KDRA2PDR	UL Listed	Open	P	480	3	4.8	6	4	4.18	3.75	TB	10	LB-IN	115	N/A	4.00
KDRA3PDR	UL Listed	Open	P	480	5	7.6	8	4	4.18	3.75	TB	10	LB-IN	115	49	4.00
KDRA4PDR	UL Listed	Open	P	480	7.5	11	12	4	4.18	3.75	TB	10	LB-IN	115	40	5.00
KDRB1PDR	UL Listed	Open	P	480	10	14	16	5	6	4	TB	20	LB-IN	115	79	7.00
KDRA31PDR	UL Listed	Open	P	575	2	2.7	4	4	4.18	3.75	TB	10	LB-IN	115	N/A	4.00
KDRA35PDR	UL Listed	Open	P	575	3	3.9	4	4	4.18	3.75	TB	10	LB-IN	115	N/A	4.00
KDRA33PDR	UL Listed	Open	P	575	5	6.1	8	4	4.18	3.75	TB	10	LB-IN	115	N/A	4.00
KDRA34PDR	UL Listed	Open	P	575	7.5	9	12	4	4.18	3.75	TB	10	LB-IN	115	N/A	4.00
KDRA36PDR	UL Listed	Open	P	575	10	11	12	4	4.18	3.75	TB	10	LB-IN	115	N/A	5.00
KDRA31PDRV	UL Recognized	Open	P	690	2	2.7	4	4.31	4.18	4.75	OD	10	LB-IN	115	N/A	4.00
KDRA35PDRV	UL Recognized	Open	P	690	3	3.9	4	4.31	4.18	4.75	OD	10	LB-IN	115	N/A	4.00
KDRA33PDRV	UL Recognized	Open	P	690	5	6.1	8	4.31	4.18	4.75	OD	10	LB-IN	115	N/A	4.00
KDRA34PDRV	UL Recognized	Open	P	690	7.5	9	12	4.31	4.18	4.75	OD	10	LB-IN	115	N/A	4.00
KDRA36PDRV	UL Recognized	Open	P	690	10	11	12	4.31	4.18	4.75	OD	10	LB-IN	115	N/A	5.00