

PART NUMBER	UL	ENCL	IMPEDANCE	RATED VOLTS	HORSE POWER	NEC AMPS	MAX CONTINUOUS AMPS	HEIGHT	WIDTH	DEPTH	TERM TYPE	TERM TORQUE	TORQUE UM	TEMP RISE	WATTS LOSS	WEIGHT
KDRMA3H1DR	UL Listed	Open	HZ	480	0.5	1.1	1.5	4.00	4.18	3.75	TB	9	LB-IN	115	9	4.00
KDRMA3L1DR	UL Listed	Open	LZ	480	0.5	1.1	1.5	4.00	4.18	3.75	TB	9	LB-IN	115	5.6	4.00
KDRMA4H1DR	UL Listed	Open	HZ	480	0.75	1.6	1.6	4.00	4.18	3.75	TB	9	LB-IN	115	15	4.00
KDRMA4L1DR	UL Listed	Open	LZ	480	0.75	1.6	1.6	4.00	4.18	3.75	TB	9	LB-IN	115	10	4.00
KDRMA5H1DR	UL Listed	Open	HZ	480	1	2.1	2.1	4.00	4.18	3.75	TB	9	LB-IN	115	12	4.00
KDRMA5L1DR	UL Listed	Open	LZ	480	1	2.1	2.1	4.00	4.18	3.75	TB	9	LB-IN	115	10.4	4.00
KDRMA6H1DR	UL Listed	Open	HZ	480	1.5	3	3	4.00	4.18	3.75	TB	9	LB-IN	115	23	4.00
KDRMA6L1DR	UL Listed	Open	LZ	480	1.5	3	3	4.00	4.18	3.75	TB	9	LB-IN	115	17	4.00
KDRAA1H2DR	UL Listed	Open	HZ	480	2	3.4	4	4.00	4.18	3.75	TB	9	LB-IN	115	33	4.00
KDRAA7L1DR	UL Listed	Open	LZ	480	2	3.4	6.4	4.00	4.18	3.75	TB	9	LB-IN	115	19	4.00
KDRAA2H2DR	UL Listed	Open	HZ	480	3	4.8	6	4.00	4.18	3.75	TB	9	LB-IN	115	38	4.00
KDRMA8L1DR	UL Listed	Open	LZ	480	3	4.8	6	4.00	4.18	3.75	TB	9	LB-IN	115	23	4.00
KDRAA3H2DR	UL Listed	Open	HZ	480	5	7.6	8	4.00	4.18	3.75	TB	9	LB-IN	115	80	4.00
KDRAA3L2DR	UL Listed	Open	LZ	480	5	7.6	9.6	4.00	4.18	3.75	TB	9	LB-IN	115	49	4.00
KDRAA4HDR	UL Listed	Open	HZ	480	7.5	11	12	4.00	4.18	3.75	TB	10	LB-IN	115	77	5.00
KDRAA4L2DR	UL Listed	Open	LZ	480	7.5	11	14	4.00	4.18	3.75	TB	9	LB-IN	115	40	4.00
KDRA5HDR	UL Listed	Open	HZ	480	10	14	14	4.00	4.18	3.75	TB	10	LB-IN	115	111	5.00
KDRA5LDR	UL Listed	Open	LZ	480	10	14	14	4.00	4.18	3.75	TB	10	LB-IN	115	64	5.00
KDRB2HDR	UL Listed	Open	HZ	480	15	21	27	5.00	6.00	4.00	TB	20	LB-IN	115	133	7.00
KDRB2LDR	UL Listed	Open	LZ	480	15	21	30	5.00	6.00	4.00	TB	20	LB-IN	115	65	8.00
KDRB1LDR	UL Listed	Open	LZ	480	20	27	30	5.00	6.00	4.00	TB	20	LB-IN	115	79	8.00