

PART NUMBER	UL	ENCL	IMPEDANCE	RATED VOLTS	HORSE POWER	NEC AMPS	MAX CONTINUOUS AMPS	HEIGHT	WIDTH	DEPTH	TERM TYPE	TERM TORQUE	TORQUE UM	TEMP RISE	WATTS LOSS	WEIGHT
KDRMA43H1DR	UL Listed	Open	HZ	575	0.5	0.9	1.5	4	4.18	3.75	TB	9	LB-IN	115	9	4.00
KDRMA43L1DR	UL Listed	Open	LZ	575	0.5	0.9	1.5	4	4.18	3.75	TB	9	LB-IN	115	6	4.00
KDRMA44H1DR	UL Listed	Open	HZ	575	0.75	1.3	2.1	4	4.18	3.75	TB	9	LB-IN	115	13	4.00
KDRMA44L1DR	UL Listed	Open	LZ	575	0.75	1.3	2.1	4	4.18	3.75	TB	9	LB-IN	115	9.3	4.00
KDRMA45H1DR	UL Listed	Open	HZ	575	1	1.7	2.1	4	4.18	3.75	TB	9	LB-IN	115	17	4.00
KDRMA45L1DR	UL Listed	Open	LZ	575	1	1.7	2.1	4	4.18	3.75	TB	9	LB-IN	115	12	4.00
KDRMA46H2DR	UL Listed	Open	HZ	575	1.5	2.4	2.8	4	4.18	3.75	TB	9	LB-IN	115	26	4.00
KDRMA46L1DR	UL Listed	Open	LZ	575	1.5	2.4	2.8	4	4.18	3.75	TB	9	LB-IN	115	19	4.00
KDRMA43H2DR	UL Listed	Open	HZ	575	2	2.7	3.2	4	4.18	3.75	TB	9	LB-IN	115	24	4.00
KDRMA47L2DR	UL Listed	Open	LZ	575	2	2.7	3.3	4	4.18	3.75	TB	9	LB-IN	115	22	4.00
KDRMA44H2DR	UL Listed	Open	HZ	575	3	3.9	5	4	4.18	3.75	TB	9	LB-IN	115	35	4.00
KDRMA47L2DR	UL Listed	Open	LZ	575	3	3.9	5	4	4.18	3.75	TB	9	LB-IN	115	23.3	4.00
KDRMA48H2DR	UL Listed	Open	HZ	575	5	6.1	7.5	4	4.18	3.75	TB	9	LB-IN	115	48	4.00
KDRMA48L2DR	UL Listed	Open	LZ	575	5	6.1	7	4	4.18	3.75	TB	9	LB-IN	115	34.7	4.00
KDRMA48L2DR	UL Listed	Open	LZ	575	7.5	9	10.4	4	4.18	3.75	TB	9	LB-IN	115	42.9	4.00
KDRB42HDR	UL Listed	Open	HZ	575	7.5	9	10	5	6	4	TB	20	LB-IN	115	61	8.00
KDRB449LDR	UL Listed	Open	LZ	575	10	11	11	4	4.18	3.75	TB	10	LB-IN	115	43.8	5.00
KDRB43HDR	UL Listed	Open	HZ	575	10	11	11	5	6	4	TB	20	LB-IN	115	71	8.00
KDRB44HDR	UL Listed	Open	HZ	575	15	17	18.5	5	6	4	TB	20	LB-IN	115	73	8.00
KDRB45LDR	UL Listed	Open	LZ	575	15	17	19.5	5	6	4	TB	20	LB-IN	115	66.2	8.00
KDRB44LDR	UL Listed	Open	LZ	575	20	22	24	5	6	4	TB	20	LB-IN	115	71.2	8.00
KDRB43LDR	UL Listed	Open	LZ	575	25	27	30	5	6	4	TB	20	LB-IN	115	76.7	8.00