

PART NUMBER	UL	ENCL	IMPEDANCE	RATED VOLTS	HORSE POWER	NEC AMPS	MAX CONTINUOUS AMPS	HEIGHT	WIDTH	DEPTH	TERM TYPE	TERM TORQUE	TORQUE UM	TEMP RISE	WATTS LOSS	WEIGHT
KDRA55HV	UL Recognized	Open	HZ	690	0.5	0.9	1.5	4	4.18	3.75	OD	10	LB-IN	115	8.9	4.00
KDRA52HV	UL Recognized	Open	HZ	690	0.75	1.3	2.1	4	4.18	3.75	OD	10	LB-IN	115	13.3	4.00
KDRA50HV	UL Recognized	Open	HZ	690	1	1.7	2.1	4	4.18	3.75	OD	10	LB-IN	115	17	4.00
KDRA51HV	UL Recognized	Open	HZ	690	1.5	2.4	2.8	4	4.18	3.75	OD	10	LB-IN	115	26.3	4.00
KDRA43HV	UL Recognized	Open	HZ	690	2	2.7	3.2	4	4.18	3.75	OD	10	LB-IN	115	23.6	4.00
KDRA44HV	UL Recognized	Open	HZ	690	3	3.9	5	4	4.18	3.75	OD	10	LB-IN	115	34.5	4.00
KDRA45HV	UL Recognized	Open	HZ	690	5	6.1	7.5	4	4.18	3.75	OD	10	LB-IN	115	47.8	4.00
KDRB42HV	UL Recognized	Open	HZ	690	7.5	9	10	5	6	4	QD	20	LB-IN	115	61.1	8.00
KDRB43HV	UL Recognized	Open	HZ	690	10	11	11	5	6	4	QD	20	LB-IN	115	70.7	8.00
KDRB44HV	UL Recognized	Open	HZ	690	15	17	18.5	5	6	4.5	RL	10	LB-IN	115	73	8.00
KDRD41HV	UL Recognized	Open	HZ	690	20	22	23	5.75	7.2	4.5	RL	20	LB-IN	115	105.6	12.00
KDRC43HV	UL Recognized	Open	HZ	690	25	27	30	5.75	7.2	5	RL	20	LB-IN	115	107.4	15.00
KDRE42HV	UL Recognized	Open	HZ	690	30	32	32	5.75	7.2	5.12	RL	20	LB-IN	115	140.3	16.00
KDRF44HV	UL Recognized	Open	HZ	690	40	41	44	7	9	6	RL	SEE DWG	LB-IN	115	172.2	30.00
KDRF45HV	UL Recognized	Open	HZ	690	50	52	58	7	9	6	RL	SEE DWG	LB-IN	115	165.6	30.00
KDRH43HV	UL Recognized	Open	HZ	690	60	62	62	8.5	11	6.5	RL	SEE DWG	LB-IN	115	205	45.00
KDRH42HV	UL Recognized	Open	HZ	690	75	77	82	8.5	11	6.5	RL	SEE DWG	LB-IN	115	251	45.00
KDRI41HV	UL Recognized	Open	HZ	690	100	99	99	9	11	7	CB	N/A	N/A	155	268	50.00
KDRG44HV	UL Recognized	Open	HZ	690	125	125	130	9	11	7.5	CB	N/A	N/A	155	381.3	65.00
KDRG45HV	UL Recognized	Open	HZ	690	150	144	155	9	11	8	CB	N/A	N/A	155	405.9	65.00
KDRJ41HV	UL Recognized	Open	HZ	690	200	192	192	9	11	9	CB	N/A	N/A	155	466.4	70.00
KDRL46HV	UL Recognized	Open	HZ	690	250	242	260	11.38	15	11	CB	N/A	N/A	155	472.3	110.00
KDRL47HV	UL Recognized	Open	HZ	690	300	289	310	11.38	15	11	CB	N/A	N/A	155	490.3	110.00
KDRL48HV	UL Recognized	Open	HZ	690	350	336	344	11.38	15	11	CB	N/A	N/A	155	539	110.00
KDRL49HV	UL Recognized	Open	HZ	690	400	382	382	11.38	15	11	CB	N/A	N/A	155	603	110.00
KDRS47HV	UL Recognized	Open	HZ	690	450	412	440	11.38	15	13	CB	N/A	N/A	155	521	165.00
KDRS46HV	UL Recognized	Open	HZ	690	500	472	500	11.38	15	13	CB	N/A	N/A	155	660.5	165.00
KDRS49HV	UL Recognized	Open	HZ	690	600	576	576	11.38	15	13	CB	N/A	N/A	155	1194	175.00
KDRX45HV	UL Recognized	Open	HZ	690	700	672	760	18.5	18.25	12.5	CB	N/A	N/A	155	1393	200.00
KDRX44HV	UL Recognized	Open	HZ	690	800	768	864	18.5	18.25	12.5	CB	N/A	N/A	155	1592	280.00
KDRX41HV	UL Recognized	Open	HZ	690	900	864	864	18.5	18.25	12.5	CB	N/A	N/A	155	1791	290.00
KDRX42HV	UL Recognized	Open	HZ	690	1000	960	1000	18.5	18.25	12.5	CB	N/A	N/A	155	1990	375.00
KDRX43HV	UL Recognized	Open	HZ	690	1100	1056	1064	18.5	18.25	12.5	CB	N/A	N/A	155	2189	450.00
KDRY41HV	UL Recognized	Open	HZ	690	1250	1200	1200	20	21	16	CB	N/A	N/A	155	2488	475.00
KDRY42HV	UL Recognized	Open	HZ	690	1500	1440	1500	20	21	16	CB	n/a	n/a	155	2985	575.00