

PART NUMBER	UL	ENCL	IMPEDANCE	RATED VOLTS	HORSE POWER	NEC AMPS	MAX CONTINUOUS AMPS	HEIGHT	WIDTH	DEPTH	TERM TYPE	TERM TORQUE	TORQUE UM	TEMP RISE	WATTS LOSS	WEIGHT
KDRA55LV	UL Recognized	Open	LZ	690	0.5	0.9	1.5	4	4.18	3.75	OD	10	LB-IN	115	6	4.00
KDRA56LV	UL Recognized	Open	LZ	690	0.75	1.3	2.1	4	4.18	3.75	OD	10	LB-IN	115	9.3	4.00
KDRA50LV	UL Recognized	Open	LZ	690	1	1.7	2.1	4	4.18	3.75	OD	10	LB-IN	115	12	4.00
KDRA51LV	UL Recognized	Open	LZ	690	1.5	2.4	2.8	4	4.18	3.75	OD	10	LB-IN	115	19	4.00
KDRA46LV	UL Recognized	Open	LZ	690	2	2.7	3.3	4	4.18	3.75	OD	10	LB-IN	115	22	4.00
KDRA52LV	UL Recognized	Open	LZ	690	3	3.9	5	4	4.18	3.75	OD	10	LB-IN	115	23.3	4.00
KDRA47LV	UL Recognized	Open	LZ	690	5	6.1	7	4	4.18	3.75	OD	10	LB-IN	115	34.7	4.00
KDRA48LV	UL Recognized	Open	LZ	690	7.5	9	10.4	4	4.18	3.75	OD	10	LB-IN	115	42.9	4.00
KDRA49LV	UL Recognized	Open	LZ	690	10	11	11	4	4.18	3.75	OD	10	LB-IN	115	43.8	5.00
KDRB45LV	UL Recognized	Open	LZ	690	15	17	19.5	5	6	4.5	RL	20	LB-IN	115	66.2	8.00
KDRB44LV	UL Recognized	Open	LZ	690	20	22	24	5	6	4.5	RL	20	LB-IN	115	71.2	8.00
KDRB43LV	UL Recognized	Open	LZ	690	25	27	30	5	6	4.5	RL	20	LB-IN	115	76.7	8.00
KDRD42LV	UL Recognized	Open	LZ	690	30	32	32	5.75	7.2	4.5	RL	20	LB-IN	115	106	12.00
KDRD43LV	UL Recognized	Open	LZ	690	40	41	41	5.75	7.2	5	RL	20	LB-IN	115	109	15.00
KDRD44LV	UL Recognized	Open	LZ	690	50	52	52	5.75	7.2	5	RL	20	LB-IN	115	123	15.00
KDRF46LV	UL Recognized	Open	LZ	690	60	62	62	7	9	6	RL	SEE DWG	LB-IN	115	181	30.00
KDRF47LV	UL Recognized	Open	LZ	690	75	77	77	7	9	6	RL	SEE DWG	LB-IN	115	194	30.00
KDRF45LV	UL Recognized	Open	LZ	690	100	99	99	7	9	6	CB	N/A	N/A	115	194	30.00
KDRH43LV	UL Recognized	Open	LZ	690	125	125	125	8.5	11	6.25	CB	N/A	N/A	115	261	45.00
KDRH44LV	UL Recognized	Open	LZ	690	150	144	144	8.5	11	6.25	CB	N/A	N/A	115	253	45.00
KDRI42LV	UL Recognized	Open	LZ	690	200	192	192	9	11	7	CB	N/A	N/A	155	342	50.00
KDRG47LV	UL Recognized	Open	LZ	690	250	242	242	9	11	8	CB	N/A	N/A	155	394	65.00
KDRG45LV	UL Recognized	Open	LZ	690	300	289	292	9	11	8	CB	N/A	N/A	155	374	65.00
KDRJ45LV	UL Recognized	Open	LZ	690	350	336	336	9	11	9	CB	N/A	N/A	155	474	70.00
KDRJ43LV	UL Recognized	Open	LZ	690	400	382	385	9	11	9	CB	N/A	N/A	155	463	70.00
KDRJ44LV	UL Recognized	Open	LZ	690	450	412	412	9	11	9	CB	N/A	N/A	155	473	70.00
KDRL45LV	UL Recognized	Open	LZ	690	500	472	480	11.38	15	11	CB	N/A	N/A	155	587	110.00
KDRL42LV	UL Recognized	Open	LZ	690	600	576	610	11.38	15	11	CB	N/A	N/A	155	716	150.00
KDRL43LV	UL Recognized	Open	LZ	690	700	672	675	11.38	15	11	CB	N/A	N/A	155	836	270.00
KDRS41LV	UL Recognized	Open	LZ	690	800	768	850	11.38	15	11	CB	N/A	N/A	155	955	275.00
KDRX41LV	UL Recognized	Open	LZ	690	900	864	900	18.5	18.25	12.5	CB	N/A	N/A	155	1075	280.00
KDRX42LV	UL Recognized	Open	LZ	690	1000	960	1000	18.5	18.25	12.5	CB	N/A	N/A	155	1194	290.00
KDRX43LV	UL Recognized	Open	LZ	690	1100	1056	1064	18.5	18.25	12.5	CB	N/A	N/A	155	1313	315.00
KDRX44LV	UL Recognized	Open	LZ	690	1250	1200	1200	18.5	18.25	12.5	CB	N/A	N/A	155	1493	325.00
KDRY41LV	UL Recognized	Open	LZ	690	1500	1440	1500	20	21	16	CB	N/A	N/A	155	1791	465.00