

PART NUMBER	UL	ENCL	IMPEDANCE	RATED VOLTS	HORSE POWER	NEC AMPS	MAX CONTINUOUS AMPS	HEIGHT	WIDTH	DEPTH	TERM TYPE	TERM TORQUE	TORQUE UM	TEMP RISE	WATTS LOSS	WEIGHT
KDRA31PV	UL Recognized	Open	P	690	2	2.7	4	4	4.18	3.75	OD	10	LB-IN	115	N/A	4.00
KDRA35PV	UL Recognized	Open	P	690	3	3.9	4	4	4.18	3.75	OD	10	LB-IN	115	N/A	4.00
KDRA33PV	UL Recognized	Open	P	690	5	6.1	8	4	4.18	3.75	OD	10	LB-IN	115	N/A	4.00
KDRA34PV	UL Recognized	Open	P	690	7.5	9	12	4	4.18	3.75	OD	10	LB-IN	115	N/A	4.00
KDRA36PV	UL Recognized	Open	P	690	10	11	12	4	4.18	3.75	OD	10	LB-IN	115	N/A	5.00
KDRD31PV	UL Recognized	Open	P	690	15	17	18	5.75	7.2	4.5	RL	20	LB-IN	115	N/A	10.00
KDRD32PV	UL Recognized	Open	P	690	20	22	25	5.75	7.2	4.5	RL	20	LB-IN	115	N/A	10.00
KDRD35PV	UL Recognized	Open	P	690	25	27	27	5.75	7.2	4.5	RL	20	LB-IN	115	N/A	10.00
KDRD33PV	UL Recognized	Open	P	690	30	32	35	5.75	7.2	4.5	RL	20	LB-IN	115	N/A	12.00
KDRD34PV	UL Recognized	Open	P	690	40	41	45	5.75	7.2	4.5	RL	20	LB-IN	115	N/A	12.00
KDRC31PV	UL Recognized	Open	P	690	50	52	55	5.75	7.2	5	RL	20	LB-IN	115	N/A	15.00
KDRF31PV	UL Recognized	Open	P	690	60	62	80	7	9	6	RL	SEE DWG	LB-IN	115	N/A	25.00
KDRF32PV	UL Recognized	Open	P	690	75	77	80	7	9	6	RL	SEE DWG	LB-IN	115	N/A	25.00
KDRF33PV	UL Recognized	Open	P	690	100	99	110	7	9	6	CB	N/A	N/A	115	N/A	30.00
KDRH31PV	UL Recognized	Open	P	690	125	125	130	8.5	11	6.25	CB	N/A	N/A	115	N/A	40.00
KDRI31PV	UL Recognized	Open	P	690	150	144	160	9	11	7	CB	N/A	N/A	155	N/A	50.00
KDRI32PV	UL Recognized	Open	P	690	200	192	200	9	11	7	CB	N/A	N/A	155	N/A	45.00
KDRG31PV	UL Recognized	Open	P	690	250	242	250	9	11	8	CB	N/A	N/A	155	N/A	60.00
KDRJ31PV	UL Recognized	Open	P	690	300	289	300	9	11	9	CB	N/A	N/A	155	N/A	70.00
KDRJ32PV	UL Recognized	Open	P	690	350	336	360	9	11	9	CB	N/A	N/A	155	N/A	70.00
KDRL31PV	UL Recognized	Open	P	690	400	382	420	11.38	14.5	9.31	CB	N/A	N/A	155	N/A	85.00
KDRL35PV	UL Recognized	Open	P	690	450	412	420	11.38	14.5	9.31	CB	N/A	N/A	155	N/A	85.00
KDRL32PV	UL Recognized	Open	P	690	500	472	480	11.38	14.5	9.31	CB	N/A	N/A	155	N/A	95.00