

PART NUMBER	ENCL	IMPEDANCE	RATED VOLTS	HORSE POWER	NEC AMPS	MAX CONTINUOUS AMPS	HEIGHT	WIDTH	DEPTH	TERM TYPE	TERM TORQUE	TORQUE UM	TEMP RISE	WATTS LOSS	WEIGHT
KDRMA6L1E3R1	E3R1	LZ	208	0.25	1.4	3.4	11.5	10	12	TB	9	LB-IN	135	26.4	16.40
KDRMA8L1E3R1	E3R1	LZ	208	0.5	2.4	5	11.5	10	12	TB	9	LB-IN	135	30.6	16.40
KDRAA3L2E3R1	E3R1	LZ	208	0.75	3.5	8.2	11.5	10	12	TB	9	LB-IN	135	44.5	18.00
KDRAA4L2E3R1	E3R1	LZ	208	1	4.6	11.6	11.5	10	12	TB	9	LB-IN	135	62.9	18.20
KDRAA4L2E3R1	E3R1	LZ	208	1.5	6.6	11.6	11.5	10	12	TB	9	LB-IN	135	62.9	18.20
KDRA27LE3R	E3R1	LZ	208	2	7.5	10	11.5	10	12	TB	10	LB-IN	135	21	19.00
KDRA28LE3R	E3R1	LZ	208	3	10.6	12	11.5	10	12	TB	10	LB-IN	135	29	19.00
KDRB22LE3R	E3R1	LZ	208	5	16.7	19	11.5	10	12	TB	20	LB-IN	135	38	23.00
KDRB23LE3R	E3R1	LZ	208	7.5	24.2	25	11.5	10	12	TB	20	LB-IN	135	48	23.00
KDRD25LE3R	E3R1	LZ	208	10	30.8	34	11.5	10	12	TB	20	LB-IN	135	64	27.00
KDRD24LE3R	E3R1	LZ	208	15	46.2	48	11.5	10	12	TB	20	LB-IN	135	85	27.00
KDRD26LE3R	E3R1	LZ	208	20	59.4	62	11.5	10	12	TB	20	LB-IN	135	94	27.00
KDRC22LE3R	E3R1	LZ	208	25	74.8	80	11.5	10	12	PT	35	LB-IN	115	114	30.00
KDRF24LE3R	E3R2	LZ	208	30	88	100	19.18	15.62	19.5	PT	120	LB-IN	115	135	67.00
KDRF25LE3R	E3R2	LZ	208	40	114	118	19.18	15.62	19.5	PT	120	LB-IN	115	149	67.00
KDRF26LE3R	E3R2	LZ	208	50	143	152	19.18	15.62	19.5	PT	275	LB-IN	115	154	67.00
KDRH22LE3R	E3R3	LZ	208	60	169	180	22.15	20.62	28.5	PT	275	LB-IN	115	209	116.00
KDRI23LE3R	E3R3	LZ	208	75	211	211	22.15	20.62	28.5	PT	500	LB-IN	155	294	126.00
KDRI24LE3R	E3R3	LZ	208	100	273	280	22.15	20.62	28.5	PT	500	LB-IN	155	276	126.00
KDRG22LE3R	E3R3	LZ	208	125	343	377	22.15	20.62	28.5	PT	275	LB-IN	155	370	145.00
KDRJ23LE3R	E3R3	LZ	208	150	396	420	22.15	20.62	28.5	PT	500	LB-IN	155	401	150.00
KDRJ24LE3R	E3R3	LZ	208	200	528	534	22.15	20.62	28.5	PT	500	LB-IN	155	442	150.00

*Ratings and dimensions are equivalent to Part Numbers containing "UL"