

PART NUMBER	ENCL	IMPEDANCE	HORSE POWER	NEC AMPS	MAX CONTINUOUS AMPS	HEIGHT	WIDTH	DEPTH	TERM TYPE	TERM TORQUE	TORQUE UM	TEMP RISE	WATTS LOSS	WEIGHT
KDRMA1H1	Open	HZ	0.25	0.7	1.4	3.63	4.45	1.78	TB	9	LB-IN	135	7.9	1.30
KDRMA2H1	Open	HZ	0.33	0.8	1.4	3.63	4.45	1.78	TB	9	LB-IN	135	9.2	1.50
KDRMA3H1	Open	HZ	0.5	1.1	1.6	3.63	4.45	1.78	TB	9	LB-IN	135	14.3	1.30
KDRMA4H1	Open	HZ	0.75	1.6	2.1	3.63	4.45	1.78	TB	9	LB-IN	135	19.3	1.40
KDRMA5H1	Open	HZ	1	2.1	2.3	3.63	4.45	1.78	TB	9	LB-IN	135	26.7	1.40
KDRMA6H1	Open	HZ	1.5	3	3.6	3.63	4.45	1.78	TB	9	LB-IN	135	30	1.60
KDRAA1H2	Open	HZ	2	3.4	3.8	4.44	4.25	2.64	TB	10	LB-IN	115	45	2.80
KDRAA2H2	Open	HZ	3	4.8	5.4	4.44	4.25	2.64	TB	10	LB-IN	115	41.8	3.00
KDRAA6H2	Open	HZ	4	6.2	7.6	4.44	4.25	2.64	TB	10	LB-IN	115	50.2	3.40
KDRAA3H2	Open	HZ	5	7.6	8.2	4.44	4.25	2.64	TB	10	LB-IN	115	80	3.70
KDRULA4H	Open	HZ	7.5	11	12	4	4.18	3.75	TB	10	LB-IN	115	77	5.00
KDRULA5H	Open	HZ	10	14	14	4	4.18	3.75	TB	10	LB-IN	115	111	5.00
KDRULB2H	Open	HZ	15	21	27	5	6	4	TB	20	LB-IN	115	133	7.00
KDRULC3H	Open	HZ	20	27	27	5.75	7.2	5	TB	20	LB-IN	115	108	15.00
KDRULC1H	Open	HZ	25	34	35	5.75	7.2	5	TB	20	LB-IN	115	112	15.00
KDRULE2H	Open	HZ	30	40	45	5.75	7.2	5	TB	20	LB-IN	115	141	16.00
KDRULF4H	Open	HZ	40	52	60	7	9	6	TB	35	LB-IN	115	169	25.00
KDRULF1H	Open	HZ	50	65	85	7	9	6	TB	35	LB-IN	115	191	25.00
KDRULF2H	Open	HZ	60	77	77	7	9	6	TB	35	LB-IN	115	226	25.00
KDRULH2H	Open	HZ	75	96	100	9	11	7.25	PT	120	LB-IN	115	212	52.00
KDRULI2H	Open	HZ	100	124	125	9	11	7	PT	120	LB-IN	155	362	52.00
KDRULG3H	Open	HZ	125	156	160	9	11	8	PT	275	LB-IN	155	274	57.00
KDRULG1H	Open	HZ	150	180	185	9	11	8.12	PT	275	LB-IN	155	359	60.00
KDRULJ1H	Open	HZ	200	240	240	9	11	9.75	PT	500	LB-IN	155	420	75.00
KDRULL1H	Open	HZ	250	302	310	11.38	14.5	9.31	PT	275	LB-IN	155	548	105.00
KDRULL2H	Open	HZ	300	361	365	11.38	14.5	11	PT	275	LB-IN	155	786	105.00
KDRULL3H	Open	HZ	350	414	435	11.38	14.5	9.31	PT	275	LB-IN	155	750	109.00
KDRULL4H	Open	HZ	400	477	480	11.38	15	12	PT	500	LB-IN	155	730	135.00
KDRULL5H	Open	HZ	450	515	540	11.38	15	12.25	PT	500	LB-IN	155	774	135.00
KDRULL6H	Open	HZ	500	590	590	11.38	15	12.25	PT	500	LB-IN	155	697	135.00
KDRULS1H	Open	HZ	600	720	750	11.38	15	13.25	PT	500	LB-IN	155	1246	272.00
KDRULS2H	Open	HZ	700	840	840	11.38	15	13.25	PT	500	LB-IN	155	1454	280.00
KDRULX2H	Open	HZ	800	960	965	18.5	21	18	PT	375	LB-IN	115	1661	305.00
KDRULX3H	Open	HZ	900	1080	1100	18.5	21	18	PT	375	LB-IN	115	1869	308.00
KDRULX4H	Open	HZ	1000	1200	1200	18.5	21	18	PT	375	LB-IN	155	1337	317.00
KDRULY2H	Open	HZ	1100	1320	1320	20	23	23	PT	375	LB-IN	115	2284	550.00
KDRULY1H	Open	HZ	1250	1500	1500	20	23	23	PT	375	LB-IN	155	2596	695.00