

PART NUMBER	ENCL	IMPEDANCE	HORSE POWER	NEC AMPS	MAX CONTINUOUS AMPS	HEIGHT	WIDTH	DEPTH	TERM TYPE	TERM TORQUE	TORQUE UM	TEMP RISE	WATTS LOSS	WEIGHT
KDRMA1L1	Open	LZ	0.25	0.7	1.4	3.63	4.45	1.78	TB	9	LB-IN	135	5	1.30
KDRMA2L1	Open	LZ	0.33	0.8	1.7	3.63	4.45	1.78	TB	9	LB-IN	135	6.2	1.30
KDRMA3L1	Open	LZ	0.5	1.1	1.6	3.63	4.45	1.78	TB	9	LB-IN	135	9.7	1.30
KDRMA4L1	Open	LZ	0.75	1.6	2.3	3.63	4.45	1.78	TB	9	LB-IN	135	12.1	1.30
KDRMA5L1	Open	LZ	1	2.1	2.3	3.63	4.45	1.78	TB	9	LB-IN	135	25.2	1.20
KDRMA6L1	Open	LZ	1.5	3	3.4	3.63	4.45	1.78	TB	9	LB-IN	135	26.4	1.40
KDRMA7L1	Open	LZ	2	3.4	4.2	3.63	4.45	1.78	TB	9	LB-IN	135	23.5	1.40
KDRMA8L1	Open	LZ	3	4.8	5	3.63	4.45	1.78	TB	9	LB-IN	135	30.6	1.40
KDRAA6L2	Open	LZ	4	6.2	7.6	4.44	4.25	2.64	TB	10	LB-IN	115	39.2	3.00
KDRAA3L2	Open	LZ	5	7.6	8.2	4.44	4.25	2.64	TB	10	LB-IN	115	48.8	3.00
KDRAA4L2	Open	LZ	7.5	11	11	4.44	4.25	2.64	TB	10	LB-IN	115	62.9	3.20
KDRULA5L	Open	LZ	10	14	14	4	4.18	3.75	TB	10	LB-IN	115	64	5.00
KDRULB2L	Open	LZ	15	21	30	5	6	4	TB	20	LB-IN	115	65	8.00
KDRULB1L	Open	LZ	20	27	30	5	6	4	TB	20	LB-IN	115	79	8.00
KDRULD1L	Open	LZ	25	34	50	5.75	7.2	4.25	TB	20	LB-IN	115	96	10.00
KDRULD2L	Open	LZ	30	40	45	5.75	7.2	4.25	TB	20	LB-IN	115	105	10.00
KDRULC1L	Open	LZ	40	52	55	5.75	7.2	5	TB	20	LB-IN	115	114	15.00
KDRULF2L	Open	LZ	50	65	65	7	9	6	TB	35	LB-IN	115	114	25.00
KDRULF4L	Open	LZ	60	77	77	7	9	6	TB	35	LB-IN	115	169	25.00
KDRULF3L	Open	LZ	75	96	110	7	9	7	PT	120	LB-IN	115	193	33.00
KDRULH3L	Open	LZ	100	124	150	9	11	7.5	PT	275	LB-IN	115	225	46.00
KDRULH2L	Open	LZ	125	156	165	9	11	7.5	PT	275	LB-IN	115	254	46.00
KDRULH1L	Open	LZ	150	180	185	9	11	7.5	PT	275	LB-IN	115	299	46.00
KDRULG3L	Open	LZ	200	240	240	9	11	9	PT	500	LB-IN	155	280	74.00
KDRULG1L	Open	LZ	250	302	340	9	11	9	PT	275	LB-IN	155	337	74.00
KDRULG2L	Open	LZ	300	361	370	9	11	9	PT	275	LB-IN	155	381	74.00
KDRULJ2L	Open	LZ	350	414	500	9	12	11.5	PT	500	LB-IN	155	465	80.00
KDRULJ1L	Open	LZ	400	477	520	9	12	11.5	PT	500	LB-IN	155	470	80.00
KDRULL1L	Open	LZ	450	515	610	11.38	15	12	PT	500	LB-IN	155	509	120.00
KDRULL2L	Open	LZ	500	590	610	11.38	15	12	PT	500	LB-IN	155	518	120.00
KDRULL3L	Open	LZ	600	720	720	11.38	14.5	9.5	PT	375	LB-IN	155	748	164.00
KDRULS1L	Open	LZ	700	840	840	11.38	15	13.25	PT	500	LB-IN	155	872	180.00
KDRULX2L	Open	LZ	800	960	965	18.5	18.25	13	PT	275	LB-IN	115	997	280.00
KDRULX3L	Open	LZ	900	1080	1080	18.5	21	18	PT	275	LB-IN	155	1121	305.00
KDRULX1L	Open	LZ	1000	1200	1200	18.5	21	18	PT	375	LB-IN	155	1246	317.00
KDRULY1L	Open	LZ	1100	1320	1350	20	23	23	PT	375	LB-IN	115	1371	502.00
KDRULY2L	Open	LZ	1250	1500	1500	20	22.8	18.7	PT	375	LB-IN	155	1558	500.00