

PART NUMBER	IMPEDANCE	HORSE POWER	AMPS	HEIGHT	WIDTH	DEPTH	TERM TYPE	TERM TORQUE	TEMP RISE	WATTS LOSS	WEIGHT
KLR2DQD1V	3	1	2	6.5	8	6	QD	N/A	115	9	8
KLR3DQD1V	3	1.5-2	3	6.5	8	6	QD	N/A	115	12	8
KLR4DQD1V	3	3	4	6.5	8	6	QD	N/A	115	18	8
KLR6DQD1V	3	3	6	6.5	8	6	QD	N/A	115	22	9
KLR8DQD1V	3	5	8	6.5	8	6	QD	N/A	115	28	11
KLR12DQD1V	3	7.5	12	6.5	8	6	QD	N/A	115	44	11
KLR16DRL1V	3	10	16	6.5	8	6	RL	N/A	115	52	12
KLR18DRL2V	3	15	18	7.5	10	7	RL	N/A	115	44	18
KLR21DRL2V	3	15	21	7.5	10	7	RL	N/A	115	51	19
KLR25DRL2V	3	20	25	7.5	10	7	RL	N/A	115	72	19
KLR27DRL2V	3	25	27	7.5	10	7	RL	N/A	115	62	19
KLR35DRL3V	3	30	35	9	12	6.13	RL	N/A	115	79	28
KLR45DRL3V	3	40	45	9	12	8	RL	N/A	115	90	38
KLR55DRL3V	3	50	55	9	12	8	RL	N/A	115	90	36
KLR80DRL4V	3	60-75	80	9	11	7.5	RL	N/A	155	116	49
KLR110DCB4V	3	100	110	15.5	15	13	CB	N/A	155	217	84
KLR130DCB4V	3	125	130	15.5	15	13	CB	N/A	155	242	82
KLR160DCB4V	3	150	160	15.5	15	13	CB	N/A	155	261	82
KLR200DCB5V	3	200	200	18.5	20	16	CB	N/A	155	270	136
KLR250DCB5V	3	250	250	18.5	20	16	TB	N/A	155	316	141
KLR300DCB5V	3	300	300	18.5	20	16	CB	N/A	155	335	151
KLR360DCB5V	3	350	360	18.5	20	16	CB	N/A	155	420	148
KLR420DCB5V	3	400	420	18.5	20	16	CB	N/A	155	435	150
KLR480DCB5V	3	500	480	18.5	20	16	CB	N/A	155	395	225
KLR600DCB5V	3	600	600	18.5	20	16	CB	N/A	155	580	200
KLR750DCB7V	3	700	750	36	28	30	CB	N/A	155	604	430
KLR850DCB7V	3	800	850	36	28	30	CB	N/A	155	703	435
KLR950DCB7V	3	900	950	36	28	30	CB	N/A	155	773	440