

PART NUMBER	TERM TYPE	HP	AMPS	Height - mm	Width - mm	Depth - mm	Weight - kg	Height - in	Width - in	Depth - in	Weight - lbs	R <sub>typ</sub> / mW	loss / W
KRF0025VTB	TB	20	25	91	236	156	4	3.59	9.3	6.15	8.8	8	17
KRF0036VTB	TB	25 - 30	36	91	236	156	4	3.59	9.3	6.15	8.8	3.8	17
KRF0050VTB	TB	40	50	91	236	156	4	3.59	9.3	6.15	8.8	2	17
KRF0080VTB	TB	50 - 75	80	141	300	171	9.5	5.56	11.82	6.74	20.9	1	22
KRF0120VTB	TB	100	120	141	348	171	10	5.56	13.71	6.74	22	0.75	37
KRF0150VTB	TB	125 - 150	150	141	348	171	10	5.56	13.71	6.74	22	0.4	31
KRF0150VCB	CB	125 - 150	150	141	260	170	13	5.56	10.24	6.7	28.6	0.14	11
KRF0180VTB	TB	125 - 150	180	141	404	171	13	5.56	15.91	6.74	28.6	0.4	45
KRF0180VCB	CB	125 - 150	180	141	260	170	13	5.56	10.24	6.7	28.6	0.14	16
KRF0250VCB	CB	200 - 250	250	115	300	190	15	4.53	11.82	7.49	33	0.063	14
KRF0320VCB	CB	300	320	116	300	260	21	4.57	11.82	10.24	46.2	0.067	24
KRF0400VCB	CB	350 - 400	400	116	300	260	21	4.57	11.82	10.24	46.2	0.067	37
KRF0600VCB	CB	450 - 500	600	116	350	260	22	4.57	13.78	10.24	48.4	0.052	65
KRF1000VCB	CB	see factory	1000	166	350	300	28	6.54	13.78	11.82	61.6	0.033	114
KRF1600VCB	CB	see factory	1600	166	350	300	34	6.54	13.78	11.82	74.8	0.022	194
KRF2500VCB	CB	see factory	2500	221.5	650	385	105	8.71	25.6	15.16	231	0.015	323

\* Suitable for 600V, 690V, and 760V applications.