

PART NUMBER	RATED VOLTS	NEC HP 480V	NEC HP 600V	NEC HP 240V	RATED CURRENT	HEIGHT	WIDTH	DEPTH	ENCL TYPE	TERM TYPE	TERM TORQUE	TORQUE UM	WATTS LOSS	WEIGHT
V1K2A03EX	600	0.75	1	-	2	11.45	10	12	3R	TB	10	LB-IN	75	25
V1K3A03EX	600	1 - 1.5	2	0.5	3	11.45	10	12	3R	TB	10	LB-IN	75	25
V1K4A03EX	600	2	3	0.75	4	11.45	10	12	3R	TB	10	LB-IN	75	25
V1K6A03EX	600	3	-	1 - 1.5	6	11.45	10	12	3R	TB	10	LB-IN	80	25
V1K8A03EX	600	5	5	2	8	11.45	10	12	3R	TB	10	LB-IN	90	25
V1K12A03EX	600	7.5	10	3	12	11.45	10	12	3R	TB	10	LB-IN	95	25
V1K16A03EX	600	10	-	5	16	11.45	10	12	3R	TB	20	LB-IN	95	29
V1K18A03EX	600	10	15	-	18	11.45	10	12	3R	TB	20	LB-IN	110	25
V1K21A03EX	600	15	-	-	21	11.45	10	12	3R	TB	20	LB-IN	110	29
V1K25A03EX	600	15	20	7.5	25	11.45	10	12	3R	TB	20	LB-IN	110	29
V1K27A03EX	600	20	25	-	27	11.45	10	12	3R	TB	20	LB-IN	110	29
V1K35A03EX	600	25	30	10	35	19.18	15.62	19.5	3R	TB	30	LB-IN	130	56
V1K45A03EX	600	30	40	15	45	19.18	15.62	19.5	3R	TB	30	LB-IN	135	56
V1K55A03EX	600	40	50	20	55	19.18	15.62	19.5	3R	TB	35	LB-IN	145	56
V1K80A03EX	600	50 - 60	75	25 - 30	80	19.18	15.62	19.5	3R	TB	35	LB-IN	255	62
V1K110A03EX	600	75	100	40	110	19.18	15.62	19.5	3R	PT	50	LB-IN	245	74
V1K130A03EX	600	100	125	50	130	19.18	15.62	19.5	3R	PT	50	LB-IN	270	89
V1K160A03EX	600	125	150	60	160	19.18	15.62	19.5	3R	PT	375	LB-IN	260	99
V1K200A03EX	600	150	200	75	200	19.18	15.62	19.5	3R	PT	50	LB-IN	265	99
V1K250A03EX	600	200	250	100	250	19.18	15.62	19.5	3R	PT	50	LB-IN	290	99
V1K305A03EX	600	250	300	-	305	22.15	20.62	28.5	3R	PT	500	LB-IN	325	109
V1K362A03EX	600	300	350	150	362	22.15	20.62	28.5	3R	PT	375	LB-IN	300	109
V1K420A03EX	600	350	450	-	420	22.15	20.62	28.5	3R	PT	500	LB-IN	450	156
V1K480A03EX	600	400	500	200	480	22.15	20.62	28.5	3R	PT	500	LB-IN	475	161
V1K600A03EX	600	500	600	-	600	36	28.21	36.86	3R	PT	500	LB-IN	515	297
V1K750A03EX	600	600	700	-	750	36	28.21	36.86	3R	PT	500	LB-IN	770	307