



Drawings:  
 General Schematic: 29853  
 Customer Connection: 25027-3  
 Interface/Display Module: 28283-1  
 Current Transformer: 26461

Notes:  
 1) Maintain 6 inch side clearance both sides for cooling.  
 2) Maintain 6 inch floor clearance for cooling.

Weight lbs (Kg): 685 (311 Kg)  
 Total Heat Loss:  
 200A: 7000 W, 23,885 Btu/h  
 250A: 8750 W, 29,856 Btu/h

The 200A unit is rated for 150A when applied with a 480V/600V autotransformer

The 250A unit is rated for 185A when applied with a 480V/600V autotransformer

				TOLERANCES (EXCEPT AS NOTED)
				DECIMAL
D	corrected weight, add encl wt.	3/13/19	MJS	.XX ± .05
C	added 600V rating notes	12/17/18	MJS	.XXX ± .025
				FRACTIONAL
B	3744 ADDED 200A INFO	9/23/16	MJS	± 1/32
A	dwg release	4/27/16	MJS	ANGULAR
NO	REVISION	DATE	BY	± 1°

**TCL** W132 N10611 Grant Drive  
 Germantown, WI 53022

OUTLINE, INSTALLATION  
 200A/250A ACTIVE FILTER TYPE 1

DRN. BY: MJS DATE: 1/13/16  
 SCALE: YES APRVD: 106131  
 SIZE: B SHT. 1 OF 1