


Drawings:
 General Schematic M/M: 29853-1
 General Schematic S/S: 29853-2
 Customer Connection: 25027-3
 Interface/Display Module: 28282-1 & 28283-1
 Current Transformer: 26461

Notes:
 Weight lbs (Kg) 798 (362).
 Front view is shown with cover removed over the converter.
 Total Heat loss:
 400A: 13,850 watts, 47,258 Btu/h.
 500A: 17,350 watts, 59,201 Btu/h.
 Interface/Display Module is supplied loose for remote mounting, cables included.
 Additional depth may be required for breaker door handle mechanism.

The 400A unit is rated for 300A when applied with a 480V/600V autotransformer.

The 500A unit is rated for 370A when applied with a 480V/600V autotransformer.

				TOLERANCES (EXCEPT AS NOTED)		W132 N10611 Grant Drive Germantown, WI 53022	
				DECIMAL		OUTLINE, INSTALLATION, 400A/500A ACTIVE FILTER, CHASSIS, No CB	
				.XX ± .05	DRN. BY		
				.XXX ± .025	MJS	APRVD:	SIZE
B	watt loss update	10/8/20	MJS	FRACTIONAL	SCALE: yes		B
A	dwg release	6/3/20	MJS	± 1/32			SHT. 1 OF 1
NO	REVISION	DATE	BY	ANGULAR			
				± 1°			