

HP	Volts	Phase	Hz.	Harmonic	Kvar	Contactor	Weight	Line Reactor Terminal Hole Size.
125	600	3	60	5TH	40	Without	300lbs	0.38 Dia Holes
125	600	3	60	5TH	40	With	305lbs	0.38 Dia Holes
150	600	3	60	5TH	45	Without	346lbs	0.44 Dia Holes
150	600	3	60	5TH	45	With	350lbs	0.44 Dia Holes

CUSTOMER CONNECTIONS:  
SEE IOM MANUAL FOR WIRE SIZE.  
FOR SCHEMATIC SEE DRAWING# 30047

L1, 2L, L3, T1, T2, T3  
SUGGESTED CUSTOMER WIRE  
ENTRY AND EXIT LOCATION.

0.50 DIA MOUNTING HOLES.  
(4 PLACES)

CUSTOMER IS RESPONSIBLE FOR INSTALLATION TO MEET  
ALL NATIONAL AND LOCAL ELECTRICAL CODES.

NOTE: USE ONLY HUBS OR FITTINGS THAT COMPLY  
WITH UL514B FOR TYPE 3R ENCLOSURES.

TOLERANCES (EXCEPT AS NOTED)			
DECIMAL			
.XX	+/-	.25	
.XXX	+/-	.1	
FRACTIONAL			
	+/-	1/16	
ANGULAR			
	+/-	1°	

**TCL**® W132 N10611 Grant Drive  
Germantown, WI 53022

**HarmonicShield, 600V  
125HP, 150HP**

DRN. BY DSW	DATE 7/22/16	DWG. No. 106604DG
SCALE 1/5	APRVD.	SHEET 1 OF 1

