



WARNING: Filter must be securely anchored to the floor to avoid tipping hazard.

The 300A unit is rated for 220A when applied with a 480V/600V autotransformer.

The 350A unit is rated for 260A when applied with a 480V/600V autotransformer.

- Notes:
- 1) Mounting hole Diameter is .64 inches
 - 2) The "A" mounting holes are mandatory. The "B" holes are optional.
 - 3) To insure proper cooling maintain 6 inch clearance on sides and front

Drawings:
 General Schematic: 31020
 Customer Connection: 25027-3
 Interface/Display Module: 28282-1 & 28283-1
 Current transformer: 26461
 Pedestal Assy Drawing: 30970

Notes:
 Weight lbs (kg) 876 (398 Kg)
 Filter/Enclosure: 835 (379 Kg)
 Pedestal: 41 (19 Kg)

Total Heat Loss:
 300A: 8,000 watts, 27,297 Btu/h.
 350A: 10,050 watts, 34,292 Btu/h.

				TOLERANCES (EXCEPT AS NOTED)	W132 N10611 Grant Drive Germantown, WI 53022
				DECIMAL	
				.XX ± .03	Outline, 300/350A Active Filter, Type 1, Floor stand
				.XXX ± .010	
C	5376 heat loss update	8/31/20	MJS	FRACTIONAL	DRN. BY: MJS DATE: 2/28/18 107579 SCALE: yes APRVD: SIZE: B
B	show new HMI Module	7/13/20	MJS	± 1/32	
A	R&D CHANGES INCORPORATED	7/17/19	MJS	ANGULAR	SHT.1 OF 1
NO	REVISION	DATE	BY	± 1°	