



V1K Part Number	Max Voltage	Amps	Phase	Weight (LBS)
V1K2A01EX*	600	2	3	11
V1K3A01EX*	600	3	3	11
V1K4A01EX*	600	4	3	11
V1K6A01EX*	600	6	3	11
V1K8A01EX*	600	8	3	11
V1K12A01EX*	600	12	3	11

\* = (Blank) - No Thermal Switch  
 \* = T - Thermal Switch Option

See V1K Installation Guide For Terminal Wire Size And Torque Information.

Note: Maintain Clearance of 3 Inches On All Sides To Other Equipment.

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES.				TOLERANCES (EXCEPT AS NOTED)				W132N10611 Grant Drive Germantown, WI 53022 © 2021 TCI, LLC	
				DECIMAL				V1K, Enclosed, Type 1, EX	
				.XX ± .25		FRACTIONAL		2 Amps To 12 Amps	
				.XXX ± .10		ANGULAR		DRN BY JRN DATE 08/02/21 109002DG	
B 6759 Update Customer Entry 08/12/24 JRN				± 1/32		SCALE TO FIT		APRVD: SIZE C	
A As Designed 08/02/21 JRN				± 1°				SHT 1 OF 1	
NO REVISION									