


|                         |                |
|-------------------------|----------------|
| 15uf 440 VOLT           | CASE MAX 70° C |
| 1 PHASE 60 HZ           | NON PCB        |
| ASC X386S(0109)6-440VAC |                |

|       |       |
|-------|-------|
| VOLTS | 60 HZ |
| 440   | 15uF  |

.25 LBS (4oz)

HOLE TOLERANCE ± .005

|    |          |         |     |                                 |   |
|----|----------|---------|-----|---------------------------------|---|
|    |          |         |     | TOLERANCES<br>(EXCEPT AS NOTED) |  W132 N10611 Grant Drive<br>Germantown, WI 53022 |
|    |          |         |     | DECIMAL                         |   |
|    |          |         |     | .XX ± .03                       | 15uF Capacitor  |
|    |          |         |     | .XXX ± .010                     |   |
|    |          |         |     | FRACTIONAL                      | DRN. BY: BWM    DATE: 4/27/16    29372<br>APRVD:    SCALE: TO FIT    SIZE: B    SHT. 1 OF 1   |
|    |          |         |     | ± 1/32                          |   |
| A  | AS DRAWN | 4/27/16 | BWM | ANGULAR                         |   |
| NO | REVISION | DATE    | BY  | ± 1°                            |   |