



480 Rated Voltage, 600 Max Voltage, High Z, Impedance.

Part Number	Horsepower (HP)	Motor Amps (A)	Maximum Amps (A)	Inductance (uH)	Weight (LBS)	Available Lug Kit	Terminal Hole Size (Inches)
KDRX2HE3R	800	960	965	32.5	645	SLK16	0.53

480 Rated Voltage, 600 Max Voltage, Low Z, Impedance.

Part Number	Horsepower (HP)	Motor Amps (A)	Maximum Amps (A)	Inductance (uH)	Weight (LBS)	Available Lug Kit	Terminal Hole Size (Inches)
KDRX2LE3R	800	960	965	19.5	620	SLK16	0.53

Customer Is Responsible For Installation to Meet All National And Local Electrical Codes.

Material(s) Shall be RoHS Compliant

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES.

NO	REVISION	DATE	BY	SCALE
B	6335, Add KDRX2HE3R	7/5/2023	DSW	
A	As Designed	5/18/2020	DSW	
NO				

DECIMAL	FRACTIONAL	ANGULAR
.XX ± .25 .XXX ± .10	± 1/32	± 1°

W132N10611 (Rev. 11/16)
 Germantown, WI 53022
 © 2023 TCI, LLC
 An **TCI** *Official Motors Company*
 KDRX--- 3 Phase, Type 3R,
 Input Line Inductors No UL.
 DSN BY: DSW DATE: 5/18/2020 FILE: 108645DG
 SCALE: 1/8 DRAWN BY: CJC SHEET 1 OF 1