



480 Rated Voltage, 600 Max Voltage, Output

Part Number	Horsepower (HP)	Maximum Amps (A)	---uH+/-10%	Weight (LBS)	Losses (W)	Terminal Hole Size (Inches)
KLR250ACB	200	250	88	91	261	0.44
KLR300ACB	250	300	74	101	291	0.44
KLR360ACB	300	360	61	98	380	0.44

Customer Is Responsible For Installation  
To Meet All National And Local Electrical Codes.  
Material(s) Shall be RoHS Compliant

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES.				TOLERANCES (EXCEPT AS NOTED)		W132N10611 (Rev 13 Feb 2024) Germantown, WI 53022 © 2024 TCI, LLC
				DECIMAL		
				FRACTIONAL		An <i>Original Motors Company</i> <b>KLR Reactors</b> L Frame
				ANGULAR		
A	6685, Drawing Was KLR-30	5/24/2024	DSW	± 1/32	DRN BY	DATE
NO	REVISION	DATE	BY	± 1°	SCALE	1/2.5
				KLR-30-2DG		SHT 1 OF 1