


CATALOG NO	VOLTS(V.)	__mH±10%	__AMPS(A)	APPROX WT-LBS
KLRUL110EPTE3R	28.75	.400	110	155
KLRUL130CPTE3R	24.0	.283	130	155
KLRUL130EPTE3R	28.75	.339	130	155




LUG WIRE RANGE 2/0-6, AL OR CU.
FOR REACTOR.
TIGHTENING TORQUE. 120 LB-IN



LABEL PLACED ON INSIDE WALL OF CABINET.



LABEL PLACED ON FRONT OF CABINET.



VENDOR LILLY POWDER COATINGS, INC.
PRODUCT CODE 312E
COLOR PEBBLE GRAY
POWDER TYPE POLYESTER POLYURETHANE

PAINT SUITABLE FOR OUTDOOR APPLICATION PER UL TYPE 3R
AND APPLIED PER A UL ACCEPTED DTV2 COATING PROGRAM.

CUSTOMER IS RESPONSIBLE FOR INSTALLATION
TO MEET ALL LOCAL AND NATIONAL CODES

				TOLERANCES EXCEPT AS NOTED	7878 N. 86th STREET MILWAUKEE, WI 53224 KLR FRAME L (ILSCO LUGS) TYPE 3R ENCLOSURE	
				DECIMAL		<small>DRN BY</small> DSW <small>DATE</small> 10/06/04 <small>DWG NO.</small> B <small>SCALE</small> TO FIT <small>APPRV.</small> <small>REV.</small>
				.XX ± .03 .XXX ± .01		
				FRACTIONAL ± 1/32		
				ANGULAR ± 1/2°	<small>REV.</small> KLRLE3R-11DG <small>SHT.</small> 1 of 1	
NO	REVISION	DATE	BY			