



CATALOG NO	VOLTS(V.)	__mH±10%	__AMPS(A)	APPROX WT-LBS
KLRUL250APT	14.40	.088	250	103
KLRUL250DPT	17.25	.106	250	103
KLRUL300APT	14.40	.074	300	113
KLRUL300DPT	17.25	.088	300	113

LUG WIRE RANGE ONE 600MCM-4  
FOR REACTOR. TWO 250MCM-1/0, AL. OR CU.  
TIGHTENING TORQUE. 500 LB-IN

**TCI** Performance and Protection for Drives.

TRANS-COIL, INC  
MILWAUKEE WI  
WWW.transcoil.com  
800-824-8282

KDR Drive Reactor  
CATALOG Motor Amps  
3PH, 60Hz, 600V Max, A Max.  
40C Amb Max, 155C Rise  
Terminal Torque LB-IN

UL US LISTED

CE

NO	REVISION	DATE	BY	TOLERANCES EXCEPT AS NOTED	7878 N. 86th STREET MILWAUKEE, WI 53224  <b>KLR UL OPEN, (FRAME L) LINE REACTOR</b>	DRN BY	DATE	DWG NO.
				DECIMAL		DRN BY <b>DSW</b> DATE <b>05/12/04</b> DWG NO. <b>BKLRULOPEN-22DG</b> SCALE <b>TO FIT</b> APPRVD.		
				.XX ± .03 .XXX ± .01				
				FRACTIONAL ± 1/32				
				ANGULAR ± 1/2°				