



Technical data and measuring conditions.

Rated Voltage $V_R$	530/310 V AC, 50/60Hz.
Rated Current $I_R$	Referred to 40 °C ambient temperature
Test Voltage $V_{test}$	2280 V DC, 2 s (line/line) 2690 V DC, 2 s (line/case)
Overload Capability (thermal)	1.5 · $I_R$ for 3 min per hour or 2.5 · $I_R$ for 30 s per hour
Leakage Current $I_{leak}$	At 530 V AC, 50 Hz.
Climatic Category (IEC 60068-1)	25/100/21 (-25 °C/+100 °C/21 days damp heat test)
Approval Standards	EN 133200, UL 1283, CSA C22.2 No. 8
Approval Markings	UR, cUR

$V_R$	$I_R$	$I_{leak}$	$R_{typ.}$	Approx. Weight
AC	A	mA	$\mu$ ohm	kg. / lbs.
530/310	150	< 20	140	13 / 28.6

			TOLERANCES (EXCEPT AS NOTED)		W132 N10611 Grant Drive Germantown, WI 53022
			DECIMAL	.XX ± .02 .XXX ± .01	
ECO 3959 ADDED			4/12/17	JRN	FRACTIONAL ± 1/32
APPROVAL MARKINGS					ANGULAR ± 1/2°
NO	REVISION	DATE	BY	SCALE TO FIT	

**KRF FILTER**  
**KRF0150ACB, 200-480V, 150A**

DRN BY: DSW    DATE: 1/04/2010    DWG. NO.: KRF0150ACB  
 SCALE: TO FIT    APRVD.:

SHT.1 OF1