




CUSTOMER CONNECTIONS

75 HP AND BELOW : USE MINIMUM 60°C COPPER WIRE
 ABOVE 75 HP : USE MINIMUM 75°C COPPER WIRE



CONTROL CONNECTIONS



TCI, LLC CLAIMS PROPRIETARY RIGHTS IN THE MATERIAL HEREIN DISCLOSED. IT IS SUPPLIED WITHOUT PREJUDICE TO ANY PATENT RIGHTS OF TCI AND MAY NOT BE REPRODUCED OR USED TO MANUFACTURE ANYTHING SHOWN THEREIN WITHOUT WRITTEN PERMISSION FROM TCI.				TOLERANCES (EXCEPT AS NOTED) DECIMAL .XX ± N/A .XXX ± N/A FRACTIONAL ± N/A ANGULAR ± N/A		TCI ® W132 N10611 Grant Drive Germantown, WI 53022 HARMONICGUARD PASSIVE 480V SCHEMATIC FAN, FUSED DISCONNECT, CONTACTOR CONTROL VERSION	
AS DESIGNED	11/05/20	JRN		DRN. BY	JRN	DATE	11/05/20
REVISION		DATE		SCALE	NONE	SIZE	
							DWG. NO. C 31462-60-100 SHT. 1 of 1